

TECHNICAL DATA SHEET

LAPL IP65 / Aga-Power-Led® Mono

VERSION - 06.05.2016


STANDARD LUMINAIRE

Reference	LAPL
Protection Class	IP65
Lighting Source	Aga-Power-Led® Mono
Connector	Festoon on B'Light conductor 16mm ²
Dimensions	75 x 67mm
Standard Length	110 - 495 - 990 - 1485 - 1980mm
Length on measure	on request up to 2970mm
Nb Lighting Unit	17 LED/m
Voltage	24V
Power	57.8 W/m
Connecting Cable	One Side: 1m cable PUR 2x1.5mm ²
Grid	Anti Glare: GAP
End Caps	EFLA

APPLICATION: Upward lighting only for Walls, Facades, Columns



LAPL / Aga-Power-Led® Mono



FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising

Glass Finishing

Standard	Clear Glass
----------	-------------

ON REQUEST

Fixation	FLP Series
Recessed Box	See Data Sheet RAPI Luminaire
Connecting Plug	AMS / AF or AMS-E / AF-E (IP68)
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

On Request: Connecting Plug

AF/AMS



AF-E/AMS-E (IP68)



LIGHTING SOURCE

Lighting Source	Aga-Power-Led® Mono
Ref	03LP22
Power	3.4W
Voltage	24V
Beam Angle	120°
CRI	80
Lifetime	60'000h
Working T°	-30°C ~ +50°C

Color Temperature & Luminous Flux / Unit

CCT	2900K	4000K
Luminous Flux/Unit	198~246 lm	243~345 lm

CERTIFICAT



AGABEKOV SA *Manufacture* 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
E - mail: info@agabekov.com

AGABEKOV



AGABEKOV SA *Bureau d'etudes* 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
Internet: www.agabekov.com

