

TECHNICAL DATA SHEET

TLFALC IP20 / Aga-Led® Type B

VERSION - 16.12.2016


STANDARD LUMINAIRE

Reference	TLFALC
Protection Class	IP20
Lighting Source	Aga-Led® Type B
Connector	4 Positions on B'Light conductor 16mm ²
Dimensions	26 x 23mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	36 LED/m
Voltage	24V
Power	34.56W/m to 43.2 W/m
Connecting Cable	1m standard cable 2x1.5mm ²

APPLICATION: cornices, handrails, stairs, shelves



TLFALC / AGA-LED® TYPE B - 4 Positions



FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling
	Powder Coating RAL
	Color Anodising
	Polished Aluminium Chrome Aspect
	Polished Aluminium Gold Aspect

ON REQUEST

Fixation	TFCP (Width: +3mm / Ht: +0.2mm)
	TFCP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX
	Ask technical departement for more information


LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2	
Ref	B3	B6
Power	0.96W	1.2W
Voltage	24V	24V
Beam Angle	120°	120°
CRI	80	80
Lifetime	50'000h	
Working T°	-20°C to +45°C	
Environmental protection	Modified acrylate resin	

Color Temperature & Luminous Flux / Unit

	2200K	2400K	2700K	3000K	4000K
Aga-Led® B3-G2	--	97 lm	137lm	137lm	137lm
Aga-Led® B6-G2	129 lm	140 lm	166 lm	166 lm	166 lm

ON REQUEST: TLFALC Fixation TFCP-S



ON REQUEST : Connecting plug AF/AMS



CERTIFICAT



AGABEKOV



AGABEKOV SA Manufacture 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
E - mail: info@agabekov.com



AGABEKOV SA Bureau d'etudes 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
Internet: www.agabekov.com

